

ORDERING FORM

FIXTURE: PTL COLE SERIES TROFFER

EXAMPLE: PTL-35W-4550L-22-4K-EM9-WH-FLK22-WMW

CODE	WATTS & LUMENS	KELVIN	OPTIONS	FINISH	ACCESSORIES	
PTL	<u>STANDARD 110</u> 28W-3080L-22 35W-3850L-22 36W-3960L-24 45W-4950L-24 50W-5500L-24 60W-6600L-24 <u>PREMIUM 130</u> 20W-2600L-22 28W-3640L-22 35W-4550L-22 35W-4550L-24 40W-5200L-24 45W-5850L-24 50W-6500L-24 60W-7800L-24 *22 - 2' X 2' 24 - 2' X 4'	3K- 3000K 35K- 3500K 4K- 4000K 5K- 5000K 6K- 6000K	EM9- Emergency 90 MIN-14W EM12- EMERGENCY 120MIN-17W	WH - WHITE	FLANGE KITS FLK22 – 2 x 2 KIT FLK24 – 2 x 4 KIT	HANGING KITS HK14-1x4 3PC KIT HK22-2x2 2PC KIT HK24-2x4 3PC KIT



PARKER LTG.



USA Company



Parker Troffer LED Cole Series

FEATURES

Longbright Driver: PF $\geq$ 0.95, THD<20%, Non-Flicker

Dimming: 0 - 10V **Voltage:** MVolt 120-277V

Emergency Battery Pack: Available in Premium Only

Lumens: 110 lm/W Standard; 130 lm/W Premium

LED Chips: Epistar, CRI>80, LM80

LED Source: SMD2835 **Beam Angle:** 120°

Color Temperature: 3000K, 3500K, 4000K, 5000K, 6000K

Material: Plastic and PC (ASTM E84)

Included: Earthquake-Proof Hook

Certification: UL, FCC, CE, RoHS

Warranty: 5 Years



ITEM NUMBER	WATT	LUMEN lm/W EMERGENCY TIME	LUMENS	DIMENSIONS	NET WEIGHT (LBS.)
PTL-20W-22-TG-02	20W	PREMIUM 130 lm/W Emergency Battery 90 min - 14W, 1820L 120 min - 17W, 2210L	2600	2' x 2'	8
PTL-28W-22-TG-02	28W		3640	2' x 2'	8
PTL-35W-22-TG-02	35W		4550	2' x 2'	8
PTL-35W-24-TG-02	35W		4550	2' x 4'	8
PTL-40W-24-TG-02	40W		5200	2' x 4'	8
PTL-45W-24-TG-02	45W		5850	2' x 4'	8.3
PTL-50W-24-TG-02	50W		6500	2' x 4'	8.3
PTL-60W-24-TG-02	60W		7800	2' x 4'	16
PTL-28W-22-TG-02	28W	STANDARD 110 lm/W Emergency Not Available for Standard	3080	2' x 2'	8
PTL-35W-22-TG-02	35W		3850	2' x 2'	8
PTL-36W-24-TG-02	36W		3960	2' x 4'	8
PTL-45W-24-TG-02	45W		4950	2' x 4'	8.3
PTL-50W-24-TG-02	50W		5500	2' x 4'	8.3
PTL-60W-24-TG-02	60W		6600	2' x 4'	16